

STEK

Technical Data Sheet

FORMULA Quartz

1. Description

- ✓ A product that coats the surface of a car to protect it from scratches and easily removes contaminants.

2. Ingredient:

Ingredient	CAS No.	% contents
Naphtha, Petroleum, Light Alkylate	64741-66-8	5-15
Toluene	108-88-3	1-5
Tert-Butyl acetate	540-88-5	25-35
Xylene	1330-20-7	5-15
Hydrotreated Light Distillate	64742-47-5	30-40
Amino-alkoxy dimethylsiloxane	71750-80-6	1-5
1,1'-Oxybisbutane; Dibutyl ether	142-96-1	<1

3. Usage Instructions

- ✓ Shake the product well before use.
- ✓ Apply enough coating agent to the applicator.
- ✓ Spread it evenly in a consistent pattern.
- ✓ For large areas like a big bonnet or roof, divide into sections.
- ✓ Avoid getting the coating on glass or plastic trim; if it does, remove it immediately.

4. Features

- ✓ - Mixing of polysilazane tailored to PPF characteristics.
- ✓ - Provides various functions such as UV protection, water repellent performance,
- ✓ chemical resistance, and self-cleaning.
- ✓ - Prevents contamination and damage, and is very effective in managing PPF.
 - Color : Clear
 - Odor : Little solvent odor
 - General Physical Form : Liquid

5. Packaging

Prod. No	Weight	Carton q"ty
	30ml	30ea

6. Personal Protection

- ✓ Wear protective gloves and goggles.

7. Storage

- ✓ Do not keep below 0 °C

Technical Information: The technical information, recommendations and other statements contained in this document are based on tests or experience that STEK believes are reliable, but the accuracy or completeness of such information is not guaranteed.

STEK

